

GLAZE PRIMER (S)

Date : 07.18

Note on English translation | This is a translation of the technical data sheet valid in Germany.
All stated details and properties are in compliance with the regulations of the German standards and building regulations.

Part 1: PRODUCT DESCRIPTION**1.1 FIELD OF APPLICATION**

Kreadiano Glaze Primer (S) is used exclusively as an optional intermediate coat / primer before using the Kreadiano Glazes (Glaze Glossy or Glaze Silicate) and the additional consolidating of the Kreadiano Lime Plaster Antika.

1.2 PROPERTIES

- silicatic primer / intermediate coat
- diffusible
- consolidating
- facilitates the processing of the Kreadiano Glazes

1.3 COLOUR

Transparent

1.4 CONSUMPTION

The consumption depends on the structure of the Lime Plaster Antika by Kreadiano.

- For smooth to slightly structured surfaces approx. 90 ml - 130 ml / m², depending on the substrate.
 - For highly structured surfaces approx. 160 ml - 200 ml / m², depending on the substrate.
- Determine exact consumption by making a sample.

1.5 DRYING (+20 °C)

Drying time at least 24 hours.

Consider longer drying times at a lower temperatures and/or higher air humidity.

1.6 STORAGE

Cool, but protected from frost. Close open containers tightly. Can be stored unopened for approx. 6 months.
Do not expose to direct sunlight or heat.

Part 2 : APPLICATION NOTES**2.1 SUBSTRATE**

The substrate must be the mineral Lime Plaster Antika of Kreadiano.

The substrates must be completely dry, clean, free of dust and free of any residual substances that may reduce the adhesion.

2.2 APPLICATION OF THE KREADIANO GLAZE PRIMER (S)

The material is ready to use. Do not dilute. Stir well before use.

Apply the Glaze Primer (S) only to complete dry Lime Plaster Antika by Kreadiano.

Apply the Glaze Primer (S) thinly (sparingly) to the Lime Plaster Antika with a roller, a sponge or a brush and thoroughly rub the Glaze Primer (S) immediately. Apply and rub quickly so that the wall surface is finished in one piece with no wiper traces.

Note: Cover surrounding areas, especially glass, clinker, natural stone, marble, painted and to be painted surfaces. Wash off splashes with water immediately. Protect eyes and sensitive skin from splashes.

GLAZE PRIMER (S)

Date : 07.18

2.3 APPLICATION CONDITIONS

During the entire application and drying time, the material, substrate and air temperature must not fall below 10 °C and not exceed 30 °C.

2.4 CLEANING TOOLS

Clean utensils immediately after use with water.

Part 3 : TECHNICAL DATA**3.1 MATERIAL BASIS**

Kaliwasserglas mit organischen Stabilisatoren. (German)
(Potassium water glass with organic stabilizers.)

3.2 COMPATIBILITY

Do not mix with other materials because its properties can possibly change significantly.

3.3 EU LIMIT VALUE FOR THE VOC CONTENT

EU limit value for the VOC content of this product (cat. A/h): 30 g/l (2010). This product contains a max. of 1 g/l VOC.

3.4 PRODUCT-CODE (GISCODES)

BSW60

3.5 WASTE CODE

080112

3.6 WATER POLLUTION CLASS

WGK 1

3.7 DISPOSAL

Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local authorities.

Part 4 : WARNING AND SAFETY ADVICE

Causes skin irritation. Causes serious eye irritation. Wear protective gloves/eye protection/face protection. Keep out of reach of children. Do not eat, drink or smoke while using the product. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of contact with eyes or skin, immediately and thoroughly rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not allow product to enter drains, waterways or soil.

This is a technical recommendation that we give to the best of our knowledge to assist the processor / purchaser based on our practical experience. The advice is non-binding, and forms no contractual, legal relationship and no additional obligations in the purchase contract. The advice does not release the purchaser from examining our products for their suitability for their foreseen uses. We reserve the right to make changes which serve to provide technical progress and improve the product or its use. When such technical information appears, earlier information is no longer valid.

KREADIANO Owner Stefan Hunold | Hirttor 10 | OT Beuren | 37327 Leinefelde - Worbis, Germany
T: +49 30 650 037 67 | **M:** info@kreadiano.de | **W:** www.kreadiano.de